



ПРОИЗВОДИТЕЛЬ ПЛАСТИКОВЫХ ВЕДЕР И КОНТЕЙНЕРОВ

Kolonia Warszawska
Al. Krakowska 96A
05-552 Wólka Kosowska
Польша

www.plastservicepack.pl

тел.: +48 (22) 756 15 86

756 15 44

факс: +48 (22) 756 17 02

handel@plastservicepack.pl

ТЕХКАРТА

W 2,5 PU

СОСТАВЛЯЮЩИЕ УПАКОВКИ	Номера форм:		
контейнер	170	227	
крышка	183	228	
ручка	192		

ВЕДРО	Номера форм:	170	227
Вес ¹		127.4г	130.0г
Номинальный объем		2500 мл	
Объем до крышки		2750 мл	
a - наружный диаметр по короне ²		157 мм	
b - внутренний диаметр по короне ²		140 мм	
c - наружный диаметр дна ²		156 мм	
h - высота контейнера ²		163 мм	
		пластик	
¹		6.0g	
		-	

¹ толерантность +/- 5% ² толерантность +/- 0,25%

КРЫШКА	Номера форм:	183	228
Вес ¹		28.0г	30.0г
Наружный диаметр ²		155 мм	155 мм
высота ²		14 мм	14 мм

¹ толерантность +/- 5% ² толерантность +/- 0,25%

УПАКОВКА ПРОДУКЦИИ	Ассортимент:	Ведро	Крышки
Количество / Евро паллет		198	2376

Другие способы упаковки доступны по индивидуальному запросу

ДЕКОРАЦИИ	Ассортимент:	Ведро	Крышки
Возможные способы печати		- / IML	- / IML

ДОПОЛНИТЕЛЬНАЯ ИНФОРМАЦИЯ	
Материал	PP / - / -
Цветовая гамма	Белый - стандарт, цвет - под заказ
Максимальное давление при 20°C	50.0 кг
Условия хранения	Контейнер общего назначения для упаковки, хранения и транспортировки жидкостей, сыпучих или жидких материалов В сухих закрытых складских помещениях, без посторонних запахов, при постоянной температуре от -5°C до + 25°C, не подверженных прямому УФ-излучению.
Заполнение	Минимальная температура ведра перед наполнением + 5°C. Максимальная температура заряда + 85°C



Цифровая техкарта
2024-02-09



General terms and conditions of use, storage, transport and filling of polypropylene packaging produced by Plast Service Pack Sp. z o. o.

The containers offered by PSP are single-use packaging. Containers are general purpose packaging, used for package, storage and transport of liquid, powdery and greasy substances.

- **Filling conditions.**

The temperature of the product during confection should be within the range of +5°C to +85°C. The containers at the time of filling must have a room temperature of approx. 20°C.

Once the confectioned product reaches a temperature of 25-30°C, the containers achieve optimal strength and stiffness, which enables the containers to be stacked according to the information provided in the specification.

The weight of the product confectioned into the container should be calculated so that the maximum pressure given to the container placed on the lowest layer at a temperature of 20°C does not exceed the value given in the specification of that packaging.

It is the customer's responsibility to validate the packaging with the target batch.

For example, the maximum static top load for W10ALDL at 20°C is 48 kg. Assuming that the input is water, where 1 L equals 1 kg, the maximum weight of the batch is 9.5 kg and the buckets can be placed in a maximum of 6 layers on the pallet.

- **Storage and transport conditions.**

The packaging should be stored in dry and closed warehouses, free of foreign odors, at a constant temperature from -5°C to +25°C, and not exposed to direct UV rays. Packagings require storage and transport tests in the target environment. The manufacturer is not responsible for the deformation of packaging and its damage resulting from the stacking of single pallets one on another or placing additional loads on them.

Packages with products inside should be carried with applied plastic or metal handle by hand. Lifting with a rope with a hook is prohibited.

- Warranty for the packaging is valid for 12 months from the date of delivery. Within this time, the packaging should be used for its intended purpose. All packages from a single pallet should be used immediately after unpacking.
- All raw materials and dyes used in the production of packaging for the food industry are approved for food contact.

Plast Service Pack Sp. z o. o. is not responsible for the use of packaging inconsistent with the intended use indicated in the packaging specification, in particular:

- for storing and transporting dangerous substances, including chemicals or boiling water;
- to carry loads in the packaging above the indicated max top load shown in the specification sheet.

Keep packaging away from children.

Use of the packaging inconsistently with its intended use may be dangerous to life or health.