



ПРОИЗВОДИТЕЛЬ ПЛАСТИКОВЫХ ВЁДЕР И КОНТЕЙНЕРОВ

Kolonia Warszawska
Al. Krakowska 96A
05-552 Wólka Kosowska
Польша

www.plastservicepack.pl

тел.: +48 (22) 756 15 86



756 15 44



факс: +48 (22) 756 17 02

handel@plastservicepack.pl


ТЕХКАРТА

W 20 ALWDL (Double Lock)

СОСТАВЛЯЮЩИЕ УПАКОВКИ		Номера форм:			
контейнер		356			
крышка		302	320	339	371
ручка		00			
ВЕДРО		Номера форм:			
Вес ¹		585.0г			
Номинальный объём		20000 мл			
Объём до крышки		21500 мл			
a - наружный диаметр по короне ²		319 мм			
b - внутренний диаметр по короне ^{>2}		302 мм			
c - наружный диаметр дна ²		276 мм			
h - высота контейнера ²		352 мм			
		пластик			
¹		23.0г			
		-			
¹ толерантность +/- 5% ² толерантность +/- 0,25%					
КРЫШКА		Номера форм:			
		302	320	339	371
Вес ¹		136.0г	135.0г	138.0г	130.0г
Наружный диаметр ²		319 мм	319 мм	319 мм	316 мм
высота ²		19 мм	19 мм	19 мм	19 мм
¹ толерантность +/- 5% ² толерантность +/- 0,25%					
УПАКОВКА ПРОДУКЦИИ		Ассортимент:			
Количество / Евро паллет		300		1200	
Другие способы упаковки доступны по индивидуальному запросу					
ДЕКОРАЦИИ		Ассортимент:			
Возможные способы печати		Офсет / IML		Офсет / IML	
ДОПОЛНИТЕЛЬНАЯ ИНФОРМАЦИЯ					
Материал		PP / PE / -  			
Цветовая гамма		Белый - стандарт,цвет - под заказ			
Защита		Double Lock - Контрольный замок первого вскрытия,край короны, защищающий от вскрытия упаковки			
Максимальное давление при 20°C		66.0 кг			
		Контейнер общего назначения для упаковки, хранения и транспортировки жидкостей, сыпучих или жидких материалов			
Условия хранения		В сухих закрытых складских помещениях, без посторонних запахов, при постоянной температуре от -5°C до + 25°C, не подверженных прямому УФ-излучению.			
Заполнение		Минимальная температура ведра перед наполнением + 5°C. Максимальная температура заряда + 85°C			



РАЗМЕЩЕНИЕ НА ЕВРОПАЛЛЕТЕ



Цифровая техкарта
2024-03-21



General terms and conditions of use, storage, transport and filling of polypropylene packaging produced by Plast Service Pack Sp. z o. o.

The containers offered by PSP are single-use packaging. Containers are general purpose packaging, used for package, storage and transport of liquid, powdery and greasy substances.

- **Filling conditions.**

The temperature of the product during confection should be within the range of +5°C to +85°C. The containers at the time of filling must have a room temperature of approx. 20°C.

Once the confectioned product reaches a temperature of 25-30°C, the containers achieve optimal strength and stiffness, which enables the containers to be stacked according to the information provided in the specification.

The weight of the product confectioned into the container should be calculated so that the maximum pressure given to the container placed on the lowest layer at a temperature of 20°C does not exceed the value given in the specification of that packaging.

It is the customer's responsibility to validate the packaging with the target batch.

For example, the maximum static top load for W10ALDL at 20°C is 48 kg. Assuming that the input is water, where 1 L equals 1 kg, the maximum weight of the batch is 9.5 kg and the buckets can be placed in a maximum of 6 layers on the pallet.

- **Storage and transport conditions.**

The packaging should be stored in dry and closed warehouses, free of foreign odors, at a constant temperature from -5°C to +25°C, and not exposed to direct UV rays. Packagings require storage and transport tests in the target environment. The manufacturer is not responsible for the deformation of packaging and its damage resulting from the stacking of single pallets one on another or placing additional loads on them.

Packages with products inside should be carried with applied plastic or metal handle by hand. Lifting with a rope with a hook is prohibited.

- Warranty for the packaging is valid for 12 months from the date of delivery. Within this time, the packaging should be used for its intended purpose. All packages from a single pallet should be used immediately after unpacking.
- All raw materials and dyes used in the production of packaging for the food industry are approved for food contact.

Plast Service Pack Sp. z o. o. is not responsible for the use of packaging inconsistent with the intended use indicated in the packaging specification, in particular:

- for storing and transporting dangerous substances, including chemicals or boiling water;
- to carry loads in the packaging above the indicated max top load shown in the specification sheet.

Keep packaging away from children.

Use of the packaging inconsistently with its intended use may be dangerous to life or health.